

**MaxX Tubing, API, Extra Heavy Duty, Closed End**

**Specifications**

- Material: HDPE
- Color: Black

**Features**

- API 5CT, Annex I, 10th edition compliant
- Advanced plastic formulation designed for durability and impact resistance
- Increased pad height and thickness for added durability
- Pin design is non-liftable; box design is liftable
- Installation/removal feature in pad design
- Designed for extreme weather conditions; tested from -50°F to 150°F
- Available in EUE thread connections only
- Fully Plastic
- 100% Recyclable



Item No.	Connection Size	Connection	Physical Attributes	Pin/ Box	Package Type	Package Qty.
27247	2 3/8	EUE 8 RD	CENLV	PIN	PLT	1080
27248	2 7/8	EUE 8 RD	CENLV	PIN	PLT	900
27249	3 1/2	EUE 8 RD	CENLV	PIN	PLT	810
26101	2	EUE 8 RD	CELV	BOX	PLT	1080
26103	2	EUE 8 RD	CELV	BOX	PLT	1690
26105	3	EUE 8 RD	CELV	BOX	PLT	891

Need to meet  
**API 5CT, ANNEX I, 10<sup>TH</sup> ED.**  
 with a different style of protector?

Check out our  
**Ultra®** and  
**Mega™** lines for  
 additional fully  
 API compliant  
 options.





### MaxX Lifiable, API, Extra Heavy Duty, Closed End



**Specifications**

- Material: HDPE
- Color: Black

**Features**

- API 5CT, Annex I, 10th edition compliant
- Advanced plastic formulation designed for durability and impact resistance
- Increased pad height and thickness for added durability
- Closed end, recessed
- Installation/removal feature in pad design
- Designed for extreme weather conditions; tested from -50°F to 150°F
- Available in API thread connections only
- Fully Plastic
- 100% Recyclable

Item No.	Connection Size	Connection	Physical Attributes	Pin/ Box	Package Type	Package Qty.
26381	4 1/2	LTC	CELV	PIN	PLT	378
26382	5 1/2	LTC	CELV	PIN	PLT	252
26123	7	LTC	CELV	PIN	PLT	100
26130	7 5/8	LTC	CELV	PIN	PLT	80
26218	8 5/8	LTC	CELV	PIN	PLT	80
26115	9 5/8	LTC	CELV	PIN	PLT	44
26217	7 5/8	STC	CELV	PIN	PLT	80
26134	8 5/8	STC	CELV	PIN	PLT	70
26114	9 5/8	STC	CELV	PIN	PLT	44
26119	10 3/4	STC	CELV	PIN	PLT	45
26153	11 3/4	STC	CELV	PIN	PLT	40
26138	13 3/8	STC	CELV	PIN	PLT	25
26109	4 1/2	STC/LTC	CELV	BOX	PLT	441
26113	5 1/2	STC/LTC	CELV	BOX	PLT	343
26125	7	STC/LTC	CELV	BOX	PLT	100
26131	7 5/8	STC/LTC	CELV	BOX	PLT	80
26135	8 5/8	STC	CELV	BOX	PLT	60
26386	8 5/8	LTC	CELV	BOX	PLT	80
26117	9 5/8	STC	CELV	BOX	PLT	44
26387	9 5/8	LTC	CELV	BOX	PLT	80
26120	10 3/4	STC	CELV	BOX	PLT	45
26154	11 3/4	STC	CELV	BOX	PLT	45
26139	13 3/8	STC	CELV	BOX	PLT	25
26380	4 1/2	BTC	CELV	PIN	PLT	384
26377	5 1/2	BTC	CELV	PIN	PLT	252
26126	7	BTC	CELV	PIN	PLT	100
26128	7 5/8	BTC	CELV	PIN	PLT	80
26132	8 5/8	BTC	CELV	PIN	PLT	60
26116	9 5/8	BTC	CELV	PIN	PLT	60
26121	10 3/4	BTC	CELV	PIN	PLT	45
26151	11 3/4	BTC	CELV	PIN	PLT	40
26136	13 3/8	BTC	CELV	PIN	PLT	25
26216	4 1/2	BTC	CELV	BOX	PLT	441
26150	5 1/2	BTC	CELV	BOX	PLT	294
26127	7	BTC	CELV	BOX	PLT	100
26129	7 5/8	BTC	CELV	BOX	PLT	80
26133	8 5/8	BTC	CELV	BOX	PLT	60
26184	9 5/8	BTC	CELV	BOX	PLT	60
26122	10 3/4	BTC	CELV	BOX	PLT	60
26152	11 3/4	BTC	CELV	BOX	PLT	40
26137	13 3/8	BTC	CELV	BOX	PLT	25

## MaxX Non-Liftable, API, Extra Heavy Duty, Closed End

### Specifications

- Material: HDPE
- Color: Black


### Features

- API 5CT, Annex I, 10th edition compliant
- Advanced plastic formulation designed for durability and impact resistance
- Ribs strategically placed to keep the diaphragm stable
- Diaphragm and pads designed to absorb and disperse energy from an impact
- Spanner holes allow the operator to safely install and remove boxes or pins using limited installation tools
- Auxiliary installation/removal feature is designed to be used with commonly found tools on a rig site
- Designed for extreme weather conditions; tested from -50°F to 150°F
- Fully Plastic
- Available in API thread connections only
- 100% Recyclable



Item No.	Connection Size	Connection	Physical Attributes	Pin/ Box	Package Type	Package Qty.
27245	4 1/2	LTC	CENLV	PIN	PLT	448
27253	5 1/2	LTC	CENLV	PIN	PLT	252
27256	7	LTC	CENLV	PIN	PLT	150
27259	9 5/8	LTC	CENLV	PIN	PLT	80
27251	4 1/2	STC	CENLV	PIN	PLT	448
27254	5 1/2	STC	CENLV	PIN	PLT	252
27258	7	STC	CENLV	PIN	PLT	150
27261	9 5/8	STC	CENLV	PIN	PLT	80
27255	5 1/2	STC/LTC	CENLV	BOX	PLT	294
27257	7	STC/LTC	CENLV	BOX	PLT	180
27262	9 5/8	STC	CENLV	BOX	PLT	80
27260	9 5/8	LTC	CENLV	BOX	PLT	80
27252	4 1/2	BTC	CENLV	PIN	PLT	384
27243	5 1/2	BTC	CENLV	PIN	PLT	252
27266	7	BTC	CENLV	PIN	PLT	150
27264	9 5/8	BTC	CENLV	PIN	PLT	80
27263	4 1/2	BTC	CENLV	BOX	PLT	441
27244	5 1/2	BTC	CENLV	BOX	PLT	252
27267	7	BTC	CENLV	BOX	PLT	150
27265	9 5/8	BTC	CENLV	BOX	PLT	80

# MAKE INSTALLATION EASIER



Contact us for your customized installation tool needs